



NOTES:

1. USE CURRENT EDITION OF THE AASHTO A POLICY ON GEOMETRIC DESIGN OF HIGHWAYS AND STREETS FOR DESIGN OF ROADWAY ELEMENTS NOT SHOWN ON THIS STANDARD DRAWING.
2. USE CURRENT EDITION OF THE AASHTO ROADSIDE DESIGN GUIDE FOR CLEAR ZONE REQUIREMENTS.
3. USE WB-67 FOR TURNING RADIUS FOR LEFT TURNS.
4. PROVIDE DRAINAGE FROM CATCH BASIN IN RAISED ISLAND AREA.
5. LANE WIDTHS SHOWN ARE TYPICAL.
6. STANDARDS SHOWN ARE RECOMMENDED VALUES. EXCEED STANDARDS IF CONDITIONS PERMIT.

REVISIONS

UTAH DEPARTMENT OF TRANSPORTATION
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION

ENTRANCE AND
EXIT RAMP AT
CROSSROADS

STD DWG
DD 5B

RECOMMENDED FOR APPROVAL
SAUL LARSEN
CHAIRMAN, STANDARDS COMMITTEE
APPROVED
DEPUTY DIRECTOR

JAN.01.2008
DATE
JAN.01.2008
DATE

STANDARD DRAWING TITLE

REMARKS

NO. DATE APPR.